

Versatile chemical protection of 15mil ,performing across a diverse range of applications

- Combining ruggedness and chemical resistance, protects workers' hands exposed to a greater variety of chemical hazards
- High performance nitrile compound ,providing an outstanding combination of chemical resistance and strength, for optimal results in wet or dry work environments
- The glove offers a far superior snag, puncture and abrasion protection,compared with rubber or neoprene gloves
- High levels of flexibility, comfort and dexterity
- Will not swell, weaken or degrade, and does not promote contact dermatitis

Industries

- Automotive
- Machinery and Equipment
- Chemical

Applications

- Handling rough machined metal parts
- Equipment repair & maintenance
- Painting or cleaning tools or robots
- Changing tools and dies
- Handling incoming goods
- Filling, blending and charging of raw materials
- Opening and draining pumps valves or lines
- Loading and unloading of proces equipment
- Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Testing
- Opening furnaces draining pumps valves or lines and crackers BTX process



AlphaTec[®] Solvex[®]


37-175

Excellent chemical protection with a good level of grip, fit and comfort

Key Features

- Cotton flocking, reducing sweat for the wearer
- Sandpatch finish giving the glove a smooth surface that decreases indirect costs, thanks to fewer rejects of fragile parts
- Fully reusable, with an unequaled abrasion resistance
- Provides superb comfort for the wearer
- Complies with FDA food handling requirements (21 CFR 177.2600)

Performance Standards



CHEMICAL AGENT	BREAKTHROUGH TIME
n-Heptane (J)	>480
Sodium hydroxide, 40% (K)	>480
Sulphuric acid, 96% (L)	52
Ammonium hydroxide, 25% (O)	232
Hydrogene peroxide, 30% (P)	>480
Formaldehyde, 37% (T)	>480

PERMEATION BREAKTHROUGH TIMES ACCORDING TO EN 16523-1 : 2015 (MINUTES)						
0	1	2	3	4	5	6
< 10	10-30	30-60	60-120	120-240	240-480	> 480
Not recommended	Splash protection		Medium protection		High protection	

Data given in the table above are based on results of laboratory tests performed on the palm area of the glove. These tests were run using standard test methods that may not adequately replicate any specific conditions of end use. Because Ansell has no detailed knowledge or control over the conditions of end use, any of these data must be advisory only, and Ansell must decline any liability.

Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec [®] Solvex [®] 37-175	Cotton Flocking, Nitrile,	6, 7, 8, 9, 10, 11	330 mm/ 13 inches	Green	• 12/polybag; 12 polybags/case

North America Region
Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
Ansell Commercial Mexico S.A. de C.V.
Blvd. Bernardo Quintana No. 7001-C,
Q7001 Torre II,
Suites 1304, 1305 y 1306,
Col. Centro Sur, c.p. 76079
Queretaro, Qro. Mexico
T: +52 442 248 1544 / 248 3133

Canada
Ansell Canada Inc.
105, rue Lauder
Cowansville (Québec)
Q7001 Torre II,
J2K 2K8, Canada
T: 1 800 363-8340
F: 1 888 267-3551

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2018 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.